

10ft Refurbished Offshore Containers – EN12079

Refrigerated container



Certified by Lloyd's Register according to the EN12079 offshore regulations. The reefer containers are designed, built, tested and certified in compliance with these norms. The lifting equipment (WLL10 tons slings set) is certified as well.

The Container box is fully reconditioned. An MPI / Load test is then carried out. These tests are according to the European standard, EN12079. Two certificates (MPI certificate and a Load test certificate) come with each container. The box is also CSC-plated according to ISO-norms (Cargo Security Certificate), which is valid for 30 months.

~Lease, lease/purchase & purchase~

Standard specifications

- Rental or sales option
- High loading capacity (volume & weight)
- Easy detachable protection frame
- High performance, reliable, machineries
- Carrier, Thermo King or Daikin machineries also stackable models available



Optional

- Cargo net
- Chill curtain
- Internal lighting
- Temperature (Partlow) recorder 5 year machinery warranty alarm



Detailed Container Specification

External Dims	Length 2991 mm x Width 2438 mm x Height 2591 mm
Internal Dims	Length 2350 mm x Width 2260 mm x Height 2260 mm
Door Opening	Width 2260 mm x Height 2200 mm
Cubic Capacity	12m ³
Max Gross Weight	10.600 Kgs
Tare Weight	2.050 Kgs
Top & Bottom Side Rail	Corten steel/M.G.S.S or Aluminium
Outside roof & Sideline	Corten steel/M.G.S.S or Aluminium
Inside Lining	High grade stainless steel
Inside floor	Aluminium T-Bar floor

Refrigeration Packages

The container is equipped with completely reconditioned Carrier 69NT40 machinery, which can both freeze and chill. The temperature range goes from -22°C up to +22°C. It is an all-electric system.
Container box

Manufacturer	Carrier
Unit Type	69NT20/40
Type of System	Picture Frame / all electric
Electrical system	380/460 Volt 50/60Hz
Cooling Capacity	at -18°C 4.9kW / +2°C 9.4kW
Power Consumption	14/16 Amp
Temp Recording	31 Day mechanical Partlow recorder
Temp Range	-22°C / +22°C at +32°C ambient
Automatic defrost	adjustable 3 – 6 – 12 or 24hrs
Compressor	6 Cylinders, 9/12.5 Hp
Refrigerant	R409a or R134a



Necessary Provisions / Remarks

The unit should be connected at 380/460V, resistor: 25Amp. Slow. The plug: 32 Amp, 4 poles (3 phase + earth)